

RECOMMENDED FLASHINGS

Flashings will be 4/12 pitch unless otherwise specified

<p>RIDGE PRO15</p> <p>7" 1/2" 15"</p>	<p>HIP PRO12</p> <p>5 1/2" 1/2" 12"</p>	<p>PEAK 636PEAK</p> <p>7" 6 1/2" 1/2" 1/2" 15"</p>	<p>EAVE 636EAVE</p> <p>3 1/4" 4 3/4" 1/2" 9"</p>
<p>GABLE 636GT</p> <p>4 1/2" 6" 1/2" 1/2" 12"</p>	<p>PROW 636PROW</p> <p>12 5/8" 1/2" 2 1/4" 15/8" 24"</p>	<p>SIDEWALL 636SW</p> <p>4" 4 1/2" 1/2" 9"</p>	<p>END WALL EW</p> <p>5 1/2" 6" 1/2" 12"</p>
<p>VALLEY WV36</p> <p>17" 1" 1" 17" 36"</p> <p>Specify if hems are needed</p>	<p>ROOF TRANSITION RT1</p> <p>5" 6 1/2" 1/2" 12"</p>	<p>ROOF TRANSITION RT2</p> <p>5" 6 1/2" 1/2" 12"</p> <p>Low slope transitions may need larger dimensions</p>	<p>WALL BASE 636DC</p> <p>3 1/4" 13/4" 1/2" 6"</p>
<p>HEADER 636HD</p> <p>3" 13/4" 1 1/2" 13/4" 9"</p>	<p>STARTER BOX 636SB</p> <p>3" 13/4" 1 1/2" 13/4" 9"</p>	<p>WALL TRANSITION 636WT</p> <p>27/8" 15/8" 1" 1/2" 6"</p>	<p>J TRIM 1 636JT1</p> <p>27/8" 1" 1/2" 15/8" 6"</p>
<p>J TRIM 2 636JT2</p> <p>23/4" 1" 15/8" 9"</p>	<p>OUTSIDE CORNER POST 636OCP</p> <p>3 1/2" 15/8" 1" 27/8" 18"</p>	<p>INSIDE CORNER POST 636ICP</p> <p>2 1/8" 15/8" 1" 2 1/2" 12"</p>	

Width	Galva/lume 26 Gauge	SMP 26 Gauge	PVDF 26 Gauge	SMP 24 Gauge	Galva/lume 24 Gauge	PVDF 24 Gauge
4"						
6"						
9"						
12"						
15"						
18"						
24"						
30"						
36"						

TERMS Net 30 Days. Prices subject to change without notice.