



ROOFNADOTM

StormTreadTM XW

RoofnadoTM StormTreadTM XW is a next generation synthetic roofing underlayment for sloped roof applications. StormTreadTM XW has an advanced mechanical slip-resistant walking surface which provides superior steep-slope walkability and increased safety for roofers. In addition, StormTreadTM XW has a uniquely designed coating technology which allows the underlayment to be anchored to the deck prior to using fasteners. StormTreadTM XW is designed for use under asphalt shingles, concrete tiles, all metal panels, synthetic shingles and primed cedar shakes. StormTreadTM XW meets all the code requirements including ASTM D226, ASTM D4869 and AC 188 as required by ICC-ES. StormTreadTM XW not only protects your roof, it helps to protect roofers as well. Ask for it at your nearest roofing distributor today.

NEXGENTM
SYNTHETICS

ALL TEMP. ALL WEATHER
PERFORMANCE



SNOW



STORMS



RAIN



HAIL



WIND



UV

- StormTreadTM XW advanced micro-etched surface technology provides superior steep-slope walkability for roofers
- All temp. all weather performance; remains flexible and easy to install in freezing or extremely hot conditions (-40° to 212°F)
- †No stretching around fasteners & no blow-offs!
- Meets the performance requirements of CAN/CSA A220.1
- ICC-ES ESR-4055 | FBC Approved – FL21895
- Class A fire rating - ASTM E108
- Texas Department of Insurance Approved
- Meets ASTM D226 Types I & II and D4869 Types II & IV
- 180 days UV exposure
- High Definition (HD) printing
- Limited Lifetime Warranty



Lifetime

LIMITED WARRANTY

StormTreadTM XW lifetime warranty



matches your premium roofing
materials warranty

SEE REVERSE
FOR MORE!



ROOFNADOTM

StormTreadTM XW

**PRINT
YOUR LOGO[®]
HERE!**

www.YOURWEB.COM

*Attract new customers
and increase awareness in
your local area!*



 **Roofnado.com**

Sentry Building Innovations

1209 Orange Street, Wilmington,
New Castle, Delaware 19801

Customer Service: 1-843-735-1773

Test/Standard*

Tensile Strength ASTM D5034
Tear Strength ASTM D4533
Liquid Water Transmission ASTM D4869
Fire Rating ASTM E108
UV Exposure
Temperature Range

Typical Value

MD 105 lbs (47.6 kg) | CD 100 lbs (45.4 kg)
MD 27 lbs (12.25 kg) | CD 24 lbs (10.9 kg)
Pass
Class A
6 Months
-40° - 212° F

Roll/Pallet Specs

Length per roll:	250' / 76.2 m
Width per roll:	48" / 1.2 m
Weight per roll:	33 lbs / 15 kg
Roll size:	10 sq / 93 m ²
Rolls per pallet/truck:	30 / 1,200
Pallet weight:	1,040 lbs / 472 kg

*Test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values \pm 10 %. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures. RN-STXW-R2 June2019

†When correctly installed as per StormTreadTM XW installation instructions. All RoofnadoTM product installation instructions are available to download or view from our website: www.roofnado.com